

DUPLEX NON-STICK TILTING BRATT PANS

- Appliance for frying and braising
- DUPLEX NON-STICK base
- Double-walled lid, spring-released and balanced as a standard
- Thermostatic temperature control regulated with control knobs
- Pan base made of a material compound with an aluminium core, plated on both sides with stainless steel (DUPLEX-NON-STICK base)
- Cleaning-friendly hygiene axles
- Motor tilting function
- Bottom unit as an H2 hygienic model
- Accurate pouring, pan emptied via integrated discharge spout
- Contactor as a standard



	FEP 611	FEP 911	FEP 921
Overall dimensions, W x D x H in mm	1100 x 850 x 900	1400 x 850 x 900	1400 x 850 x 900
Weight in kg	220	275	389
Electrical connection in kW 400 V 3N 50/60 Hz	10.85	16.25	21.75
Pan made of stainless steel, DUPLEX NON-STICK base, W x D x H in mm	616 x 660 x 184	928 x 660 x 184	928 x 640 x 402
Maximum capacity in litres	69	109	247
Usable capacity in litres	53	83	220
Frying surface in m ²	0.41	0.61	0.59
Double-walled lid	●	●	●
Contactor	●	●	●
Hygienic bottom structure H2	●	●	●

OPTION

VAR 479 Mixing tap 3/4"	○	○	○
-------------------------	---	---	---

ACCESSORIES

ZUB F46 Mixing tap 3/4" (assembly set)	○	○	○
ZUB 961 Swivel tap 3/4" for WW, radial excursion 300 mm, height 80/390 mm (assembly set)	○	○	○
ZUB 960 Swivel tap 1/2" for WW, radial excursion (assembly set)	○	○	○
ZUB M50 Shovel unperforated, 180 x 130 mm, nominal capacity 2 liters	○	○	○
ZUB M51 Shovel perforated, 180 x 130 mm, nominal capacity 2 liters	○	○	○
ZUB M52 Spatula, width 250 mm	○	○	○

○ = Optional (price on request)