

GAS DUPLEX NON-STICK TILTING BRATT PANS



- Multifunctional appliance for frying, braising and cooking
- Innovative 📧 touch panel
- DUPLEX NON-STICK base
- With a double-walled lid as a standard, spring-released, balanced
- Electronic temperature controls with set and actual temperature display and 3 fast activation settings each for the cooking time and temperature
- Pan base made of a material compound with an aluminium core, plated on both sides with stainless steel (DUPLEX non-stick base)
- Pan made completely of stainless steel, with 4-point temperature control
- Cleaning-friendly hygiene axles
- Motor tilting function
- Bottom unit as a H2 hygienic model
- Accurate pouring, pan emptied via integrated discharge spout





| | FGP 610 | FGP 910 |
|---|------------------|------------------|
| Overall dimensions, W × D × H in mm | 1100 × 850 × 900 | 1400 × 850 × 900 |
| Weight in kg | 251 | 321 |
| Nominal heat load in kW natural gas E, 20 mbar | 18 | 24 |
| Electrical connection in kW 230 V 1N 50/60 Hz | 0.3 | 0.3 |
| Pan made completely of stainless steel, DUPLEX NON-STICK base with 4-point temperature control, W \times D \times H in mm | 616 × 660 × 184 | 928 × 660 × 184 |
| Maximum capacity in litres | 69 | 109 |
| Usable capacity in litres | 53 | 83 |
| Frying surface in m ² | 0.41 | 0.61 |
| Double-walled lid | • | • |
| Hygienic bottom structure H2 | • | • |
| STANDARD ACCESSORY | | |
| 1 stainless-steel-clad safety gas tube | • | • |

| | TOP OPTION |
|---|------------|
| U | TOPOPITON |

VAR 320 Volume-regulated water intake device with a mixing tap (cold, warm and mixed water)

- Water automatically filled to the exact litre
- Rapid selection of various filling quantities with a Boutouch panel
- 0 0 • Automatic filling process stop

OPTION

| VAR 479 Mixing tap ¾" | _ 0 | <u> </u> |
|--|-----|----------|
| ACCESSORIES | | |
| ZUB F46 Mixing tap ¾" (assembly set) | 0 | 0 |
| ZUB 961 Swivel tap ¾" for WW, radial excursion 300 mm, height 80/390 mm (assembly set) | 0 | 0 |
| ZUB 960 Swivel tap $\frac{1}{2}$ " for WW, radial excursion (assembly set) | 0 | 0 |
| 7UB 832 Safety gas tube 1/2" 600 mm for connection through the rear wall | 0 | 0 |

| ZUB 961 Swivel tap ¾" for WW, radial excursion 300 mm, height 80/390 mm (assembly set) | 0 | 0 |
|--|-------------|-------------|
| ZUB 960 Swivel tap ½" for WW, radial excursion (assembly set) | 0 | 0 |
| ZUB 832 Safety gas tube ½", 600 mm for connection through the rear wall | 0 | 0 |
| Injector sets for different gas types | see page 69 | see page 69 |
| ZUB M50 Shovel unperforated, 180 × 130 mm, nominal capacity 2 liters | 0 | 0 |
| ZUB M51 Shovel perforated, 180 × 130 mm, nominal capacity 2 liters | 0 | 0 |
| ZUB M52 Spatula, width 250 mm | 0 | 0 |

O = Optional (price on request)

04/2021