



**GAS FAST BOILING PANS**

- Innovative touch panel control
- Gas blower technology for maximum effect and economy
- Electronic temperature controls with set and actual temperature display and 3 fast activation settings each for the cooking time and temperature
- Double-walled lid, spring-released, balanced
- Inner pan made of CrNiMoTi steel 1.4571
- Inner pan emptied via safety discharge valve DN 40 (1 1/2")
- Cover plate drained via overflow pipe
- Water inlet via a lid-operated swivel tap, mixing tap with cold and hot water valve
- Filling level marking with 5-litre graduations
- Integrated gas connection and shut-off valve



	<b>FLS 060</b>	<b>FLS 100</b>	<b>FLS 150</b>
Overall dimensions, W x D x H in mm	800 x 850 x 900	900 x 850 x 900	1100 x 850 x 900
Weight in kg	132	153	180
Nominal heat load in kW natural gas E, 20 mbar	16	23	27
Electrical connection in kW 230 V 1N 50/60 Hz	0.3	0.3	0.3
Usable capacity in litres	63.5	109	155
Inner pan diameter in mm	484	584	697
Inner pan height in mm	410	470	470
<b>Boiling time, determined to DIN 18855, in minutes</b>	<b>22</b>	<b>26</b>	<b>33</b>
Fast boiling pan according to DIN 18855	●	●	●

**STANDARD ACCESSORY**

1 strainer	●	●	●
2 stainless-steel-clad pressure hoses for drinking water	●	●	●
1 stainless-steel-clad safety gas tube	●	●	●

**TOP OPTION**

**VAR 320 Volume-regulated water intake device (cold, warm and mixed water)**

• Water automatically filled to the exact litre			
• Rapid selection of various filling quantities with a  touch panel			
• Automatic filling process stop	○	○	○

**VAR 808 Core temperature probe**

• Cooking to perfection			
• Rapid selection of various temperatures with a  touch panel			
• Save on energy through optimal cooking time	○	○	○

**ACCESSORIES**

ZUB 791 Doppelmantel für Abgaskamin	○	○	○
ZUB 320 1 pair of lifting hooks	○	○	○
ZUB 322 Support ring for inserts	○		
ZUB 323 Support ring for inserts		○	
ZUB 324 Support ring for inserts			○
<b>Inserts, 8 mm perforation (up to 2 inserts per appliance)</b>			
ZUB 382 1 insert, diameter 465 mm, height 150 mm	○		
ZUB 384 1 insert, diameter 565 mm, height 180 mm		○	
ZUB 389 1 insert, diameter 675 mm, divided, height 180 mm			○
<b>Inserts, 2.5 mm perforation (up to 2 inserts per appliance)</b>			
ZUB 392 1 insert, diameter 465 mm, height 150 mm	○		
ZUB 394 1 insert, diameter 565 mm, height 180 mm		○	
ZUB 399 1 insert, diameter 675 mm, divided, height 180 mm			○
Injector sets for different gas types	see page 69	see page 69	see page 69

○ = Optional (price on request)