

LOW-PRESSURE STEAM RECTANGULAR BOILING PANS

- Manual valve for steam feed
- Temperature of the food adjusted manually
- Double-walled lid, spring-released and balanced with all-round seal made of temperature-resistant elastomer
- Inner pan made of CrNiMoTi steel 1.4571
- Inner pan emptied via safety discharge valve DN 50 (2")
- Cover plate drained via overflow pipe
- Water inlet via a lid-operated swivel tap, mixing tap with cold and hot water valve
- Heating by direct steam supply, 0.3 – 0.5 bar gauge pressure
- Filling level marking with 25-litre graduations



	FNR 301	FNR 401
Overall dimensions, W x D x H in mm	1600 x 850 x 900	2100 x 850 x 900
Weight in kg	256	322
Rated output in kW	49.0 at 78 kg/h	60.0 at 96 kg/h
Usable capacity in litres	294	422
Dimensions of inner pan, W x D x H in mm	1150 x 660 x 435	1650 x 660 x 435
Capacity of inserts GN 1/1, 200 mm	8 Units	12 Units
Boiling time, determined to DIN 18855, in minutes (at 0.5 bar gauge pressure)	35	38.5

STANDARD ACCESSORY

1 strainer	●	●
2 stainless-steel-clad pressure hoses for drinking water	●	●
1 stainless-steel-clad pressure hose for supply of low-pressure steam	●	●

OPTION

VAR 303 Built-in steam separator	○	○
----------------------------------	---	---

ACCESSORIES

ZUB 679 Container support	○	
ZUB 680 Container support		○

○ = Optional (price on request)

