

LOW-PRESSURE STEAM RECTANGULAR FAST BOILING PANS

- Manual valve for steam feed
- Temperature of the food adjusted manually
- Double-walled lid, spring-released and balanced with all-round seal made of temperature-resistant elastomer
- Inner pan made of CrNiMoTi steel 1.4571
- Inner pan emptied via safety discharge valve DN 50 (2")
- Cover plate drained via overflow pipe
- Water inlet via a lid-operated swivel tap, mixing tap with cold and hot water valve
- Heating by direct steam supply, 0.3 – 0.5 bar gauge pressure
- Filling level marking with 10-litre graduations on FNR 151, 25-litre graduations on FNR 251



	<b>FNR 151</b>	<b>FNR 251</b>
Overall dimensions, W x D x H in mm	1100 x 850 x 900	1400 x 850 x 900
Weight in kg	183	220
Rated output in kW	40.0 at 64 kg/h	44.0 at 70 kg/h
Usable capacity in litres	158	253
Dimensions of inner pan, W x D x H in mm	620 x 660 x 435	990 x 660 x 435
Capacity of inserts GN 1/1, 200 mm	4 Units	6 Units
Fast boiling pan according to DIN 18855	●	●
Boiling time, determined to DIN 18855, in minutes (at 0.5 bar gauge pressure)	21.5	33

**STANDARD ACCESSORY**

1 strainer	●	●
2 stainless-steel-clad pressure hoses for drinking water	●	●
1 stainless-steel-clad pressure hose for supply of low-pressure steam	●	●

**OPTION**

VAR 303 Built-in steam separator	○	○
----------------------------------	---	---

**ACCESSORIES**

ZUB 677 Container support	○	
ZUB 678 Container support		○

○ = Optional (price on request)

